

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
2 June 2005 (02.06.2005)

PCT

(10) International Publication Number
WO 2005/049366 A1

(51) International Patent Classification⁷: **B60L 3/00,**
G01R 31/00

[JP/JP]; c/o Toyota Jidosha Kabushiki Kaisha, 1, Toyota-cho, Toyota-shi, Aichi-ken 471-8571 (JP).

(21) International Application Number:
PCT/JP2004/003550

(22) International Filing Date: 29 October 2004 (29.10.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003-389644 19 November 2003 (19.11.2003) JP

(71) Applicant (for all designated States except US): **TOYOTA JIDOSHA KABUSHIKI KAISHA** [JP/JP]; 1, Toyota-cho, Toyota-shi, Aichi-ken 471-8571 (JP).

(72) Inventor; and


(75) Inventor/Applicant (for US only): **NOZAKI, Takeshi**

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: **ABNORMALITY MONITORING APPARATUS IN LOAD DRIVE CIRCUIT**



(57) Abstract: An ECU performs a program. In the program, in the case where a converter is performing an operation for increasing a voltage (i.e., YES in step S 102), when a difference between an estimated battery voltage VBE and a battery voltage VB has continued to be large (i.e., YES in step S 104), the ECU tentatively determines that a battery voltage sensor is abnormal (S 106), and stops voltage increasing control for the converter (S 108). If an absolute value of a difference between a battery voltage and an output side voltage is large (i.e., YES in step S 110), a difference A which is an absolute value between an estimated battery voltage and a battery voltage, and a difference B which is an absolute value between the estimated battery voltage and an output side voltage are calculated (S 112). If a value obtained by subtracting the difference B from the difference A has continued to be large (i.e., YES in step S 114), it is determined that the battery voltage sensor is abnormal (S 116). If a voltage obtained by subtracting the difference A from the difference B has continued to be large (i.e., YES in step S 118), it is determined that the output side voltage sensor is

WO 2005/049366 A1



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.